



5206 Bearing 2D drawings and 3D CAD models

30 mm x 62 mm x 23.8 mm F-566427.H195 Truck Bearing

Bearing No. 5206

Size	30x62x23.8 mm
Bore Diameter	30 mm
Outer Diameter	62 mm
Width	23.8 mm
d	30 mm
D	62 mm
B	23.8 mm
C	23.8 mm
a	30.8 mm
r min.	1 mm
da min.	35.5 mm
da max	38.6 mm
Da max.	56.5 mm
ra max.	1 mm
Weight	0.290 Kg
Basic dynamic load rating (C)	29.7 kN
Basic static load rating (C0)	21.3 kN
(Grease) Lubrication Speed	6400 r/min
Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0.321
Product Group	B00152



UG Ball Bearing CORP.

Enclosure	Open
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Double Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	24 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch - Metric	Metric
Long Description	30MM Bore; 62MM Outside Diameter; 23.8MM Width; Open; No Flush Ground; Ball Bearing; Double Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; C0-Medium; Steel Cage; 24 Degree; 1 (Single)
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.koyousa.com
Width	0.937 Inch 23.8 Millimeter
Outside Diameter	2.441 Inch 62 Millimeter
Bore	1.181 Inch 30 Millimeter
Bearing No.	5206
r(min)	1
Cr	37.2



UG Ball Bearing CORP.

C0r	21.3
Cu	1.10
Grease lub.	6400
Oil lub.	8600
da(min)	35.5
da(max)	-
Da(max)	56.5
ra(max)	1
(Refer.) Mass(kg)	0.290